

# MATERIAL SAFETY DATA SHEET

**Rainguard Plugger 10%**

Page 1 of 3

## =====SECTION I - MANUFACTURER IDENTIFICATION=====

MANUFACTURER'S NAME: Weatherman Products, Inc  
1079 Culpepper Drive  
Conyers GA 30094

EMERGENCY PHONE: 800-272-4647

## ====SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION====

REPORTABLE COMPONENTS	CAS NUMBER	WEIGHT %	PEL
-----------------------	------------	----------	-----

---

\*\*\*No toxic chemical(s) subject to the reporting requirements of section 313 of Title and of CFR 372 are present.\*\*

## =====SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS=====

BOILING RANGE:	212F
SPECIFIC GRAVITY (H <sub>2</sub> O=1)	1.28
VAPOR DENSITY:	heavier than air
EVAPORATION RATE:	slower than ether
COATING V.O.C:	less than 20 grams per liter
SOLUBILITY IN WATER:	soluble.
APPEARANCE AND ODOR:	colored liquid with sweet odor.

## =====SECTION IV - FIRE AND EXPLOSION HAZARD DATA=====

FLASH POINT:	WATER BORNE-N/A
FLAMMABLE LIMITS IN AIR:	N/A
EXTINGUISHING MEDIA:	dried coating will burn like plastic, use foam, co <sub>2</sub> , water fog
SPECIAL FIREFIGHTING PROCEDURES	Respiratory equipment should be worn to avoid inhalation of concentrated vapors.
UNUSUAL FIRE AND EXPLOSION HAZARDS	Heated cans can build up pressure and explode.

## =====SECTION V - REACTIVITY DATA=====

STABILITY:	stable
CONDITIONS TO AVOID:	Excessive heat, poor ventilation, corrosive atmospheres, excessive aging.
INCOMPATIBILITY (MATERIALS TO AVOID) HAZ DECOMPOSITION OR BYPRODUCTS	Strong chemicals and oxidizing materials. Carbon monoxide, carbon dioxide, oxides of nitrogen.
HAZARDOUS POLYMERIZATION:	Will not occur.

# MATERIAL SAFETY DATA SHEET

**Rainguard Plugger 10%**

Page 2 of 3

## =====SECTION VI - HEALTH HAZARD DATA=====

### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation: Dizziness, breathing difficulty, headaches & loss of coordination.

### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Eye contact: Irritation, tearing, redness and blurred vision.

### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin contact: Can dry and defat skin causing cracks, irritation and dermatitis.

### INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion: Can cause gastrointestinal irritation, vomiting, nausea, and diarrhea.

### HEALTH HAZARDS (ACUTE AND CHRONIC)

Inhalation-Dizziness, breathing difficulty, headaches, & loss of coordination. Eye contact-Irritation, tearing, redness, and blurred vision. Skin contact-Can dry and defat skin causing cracks, irritation, and dermatitis. Ingestion-can cause gastrointestinal irritation, vomiting, nausea, & diarrhea. Chronic: Liver damage has been known to occur with concentrated overexposure to solvents.

CARCINOGENICITY: NTP: no IARC: no OSHA: no

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Asthma, Emphysema.

### EMERGENCY AND FIRST AID PROCEDURES

Inhalation overexposure-move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention. Eye contact-flush with large quantities of water for 15 minutes. Skin contact-wash thoroughly with soap and water and see a doctor. Ingestion-Do not induce vomiting, can cause chemical pneumonitis and pulmonary edema. Contact physician immediately.

## =====SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE=====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate ignition sources, provide good ventilation, dike spill area and add absorbent earth or sawdust to spilled liquid. Thoroughly wet with water and mix

### WASTE DISPOSAL METHOD

Collect absorbent/water/spilled liquid mixture into metal containers and add enough water to cover. Consult local, state & federal hazardous waste regulations before disposing into approved hazardous waste landfills. Obey relevant laws.

# MATERIAL SAFETY DATA SHEET

**Rainguard Plugger 10%**

Page 3 of 3

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Use in cool, well-ventilated areas. Keep containers closed when not in use.

## OTHER PRECAUTIONS

After using this product, wash hands before smoking or eating.

## =====SECTION VIII - CONTROL MEASURES=====

### RESPIRATORY PROTECTION

Use cartridge respirator to filter the particulates and cosolvent vapors.

### VENTILATION

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below the PEL and TLV.

### PROTECTIVE GLOVES

Use impermeable chemical handling gloves for skin protection.

### EYE PROTECTION

Use chemical safety glasses, goggles, and face shields for eye protection.

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Use impermeable aprons and protective clothing whenever possible to prevent skin contact. The use of head caps whenever possible is strongly recommended.

## =====SECTION IX - DISCLAIMER=====

THE INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT THAT IT IS ACCURATE TO THE BEST OF AMERICAN PAINT COMPANY'S KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED BY AMERICAN PAINT COMPANY TO BE ACCURATE. AMERICAN PAINT COMPANY DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR USE OR RELIANCE ON THIS INFORMATION. CUSTOMERS ARE ENCOURAGED TO CONDUCT THEIR OWN TESTS. BEFORE USING ANY PRODUCT, READ ITS' LABEL.